



Safety Data Sheet

C200 EURO CLEAR

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

TOUCAN C200 EURO CLEAR HS

Contains: Butyl acetate, Methyl acetate, 4-chloro- α,α,α -trifluorotoluene

1.2. Relevant identified uses of the substance or mixture and uses advised against

Two component clear coat for car bodies

1.3. Details of the supplier of the safety data sheet

COMPANY IDENTITY: Logicar Inc.
COMPANY ADDRESS: 1361 NW 155th DR
COMPANY CITY: Miami, FL 33169
COMPANY PHONE: 305-685-8044

1.4. Emergency telephone number

CHEMTREC: +1(703)527-3887

Section 2: Hazards identification

2.1. Classification of the substance or mixture

The product was classified as dangerous according to Regulation 1272/2008/EC

Classification:

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2 H319

STOT SE 3 H335

STOT SE 3 H336

2.2. Label elements



Signal word: DANGER



Safety Data Sheet

C200 EURO CLEAR

Hazard statements:

H225 Very flammable liquid and vapour
 H315 Causes skin irritation
 H319 Causes serious eye irritation
 H335 May cause respiratory irritation
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container to an authorized waste collection point.

Section 3: Composition/information on ingredients

3.1. Mixtures

Index number	Chemical Name	WE Number	CAS Number	Classification of substance according to CLP	Mark of substance	Weight	Registration Number
607-025-00-1	Butyl acetate	204-658-1	123-86-4	Flam. Liq. 3 H226 STOT SE 3 H336	GHS02 GHS07 Wng H226, H336, EUH066	15 – 25%	01- 2119485493- 29-XXXX
607-021-00-X	Methyl acetate	203-933-3	79-20-9	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336	GHS02 GHS07 Dgr H225, H319, H336, EUH066	15 – 25%	01- 2119459211- 47-XXXX
-	4-chloro- <i>o,o</i> , <i>o</i> -trifluorotoluene	202-681-1	98-56-6	Flam. Liq. 3 H226 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315	GHS02 GHS07 H226, H315, H319, H335	5 – 15%	01- 2119857280- 40-XXXX
601-022-00-9	Xylene	215-535-7	1330-20-7	Flam. Liq. 3 H226 Acute Tox. 4 * H332 Acute Tox. 4 * H312 Skin Irrit. 2 H315	GHS02 GHS07 Wng H226, H312, H315, H332	0 – 5%	01- 2119488216- 32-XXXX



Safety Data Sheet

C200 EURO CLEAR

Section 4: First aid measures

4.1. Description of first aid measures

General information:	See 11 point SDS
Inhalation:	Move to fresh air, ensure quiet and warmth, seek medical advice.
Eyes contact:	Do not close the eye, rinse with plenty of water (protect) healthy eye, remove contact lenses, seek medical advice.
Skin contact:	Immediately remove all contaminated clothing, wash with plenty of water with soap, seek medical advice.
Ingestion:	Wash out mouth thoroughly with water. Do not induce the vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Seek medical advice

4.3. Indication of any immediate medical attention and special treatment needed

Seek medical advice

Section 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media:	Water, vaporised water, foam, CO ₂ .
Unsuitable extinguishing media:	Tight stream of water.

5.2. Special hazards arising from the substance or mixture

Under the influence of high temperature may produce CO, CO₂ vapours.

5.3. Advice for fire-fighters

Firemen have to wear self-contained breathing apparatus and protective clothing. Cool adjacent tanks by spraying water from a safe distance.



Safety Data Sheet

C200 EURO CLEAR

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Remove ignition sources. Provide for sufficient ventilation. Avoid direct contact with releasing substance (vapours). Avoid contact with eyes and skin. Get acquainted with safety conditions (see point 7 and 8 SDS).
For emergency responders:

6.2. Environmental precautions

Keep away from drains, surface-water, ground-water and soil.

6.3. Methods and material for containment and cleaning up

Poured substance should be absorbed with non-flammable materials: sand, silica, special granulated products. Keep to a minimum efflux area. Collect discards, store according to regulations (see point 13 SDS).

Section 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat; keep away from sources of ignition – do not smoke, do not eat, do not drink, do not breathe vapour, avoid contact with skin and eyes. Do not empty under pressure. Use only original tanks.

7.2. Conditions for safe storage, including any incompatibilities

Normal precautions taken when handling flammable substances. Store in hermetically closed containers in temp. 5°-25°C. Place of storage should be dry. Protect from heat. Do not store near to sources of ignition.

7.3. Specific end use(s)

Two component clear coat for car bodies.



Safety Data Sheet

C200 EURO CLEAR

Section 8: Exposure controls/personal protection

8.1. Control parameters

Limit values for Butyl acetate:	TLV: 150 ppm as TWA 200 ppm as STEL (ACGIH 2003). MAK: 100 ppm 480 mg/m ³
Limit values for Xylene	TLV: 100 ppm as TWA 150 ppm as STEL A4 (ACGIH 2001). BEI (ACGIH 2001). EU Limit Values: 50 ppm 221 mg/m ³ (8 hours) 100 ppm 442 mg/m ³ (short-term) skin

8.2. Exposure controls

Respiratory protection:	Gas mask with "A" type absorbing canister.
Hands protection:	Protective gloves for handling solvents (nitrile rubber).
Eyes protection:	Protective glasses.
Skin protection:	Suitable protective clothing.
Workplace:	Topical stays and exhausting ventilation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid	Auto ignition point: no data
Colour: colourless	Vapour pressure: no data
Odour: typical mixture of solvents	Explosion limits: no data
pH: no data	Density: 1,033 g/cm ³
Boiling point: > 56°C	Water solubility: very poor
Melting point: no data	Octanol/Water partition coeff: no data
Flash point: < 0°C	Viscosity: 15±2" Ford Cup DIN 4

9.2. Other information

VOC
< 4.2 lb/gal



Safety Data Sheet

C200 EURO CLEAR

Section 10: Stability and reactivity

10.1. Reactivity

No data.

10.2. Chemical stability

If handled according to the section 7 product is stable.

10.3. Possibility of hazardous reactions

No data.

10.4. Conditions to avoid

Strong acids and basis, high temperature, peroxides, amines, alcohols.

10.5. Incompatible materials

No data.

10.6. Hazardous decomposition products

Incomplete combustion will produce CO, CO₂ and toxic gases.



Safety Data Sheet

C200 EURO CLEAR

Section 11: Toxicological information

11.1. Information on toxicological effects

There are no data on the toxicity of this product.

Symptoms / routes of exposure

Toxicity for Butyl acetate:	LD ₅₀ (rat, oral) – 6400 mg/kg LC ₅₀ (rat, inhalation) – 9,6 mg/l (4h) LD ₅₀ (rabbit, skin) – >5000 mg/kg
Toxicity for 4-chloro- α,α,α -trifluorotoluene:	LD ₅₀ (rat, oral) – 13000 mg/kg LC ₅₀ (rat, inhalation) – 33 mg/l (4 h) LD ₅₀ (rabbit, skin) > 2 mg/kg
Irritating effect:	Skin: irritating and dryness Eyes: irritating
Symptoms of poisoning:	Headaches, discomfort, tiredness, sleepiness, vomiting or may narcotise, muscle failure, partial or total loss of consciousness.

Section 12: Ecological information

12.1. Toxicity

Butyl acetate acute toxicity for:	(LC ₅₀ /96 h) fish – 62 mg/l (EC ₅₀ /48h) crustacea – 32 mg/l
4-chloro- α,α,α -trifluorotoluene acute toxicity for:	(LC ₅₀ /24 h) fish – 15,9 – 22,9 mg/l (EC ₅₀ /24h) crustacea – 3,68 mg/l

The product is very poorly soluble in water. Do not allow to enter the sewage system, soil, or water reservoirs – inform the local authorities.



Safety Data Sheet

C200 EURO CLEAR

Section 13: Disposal considerations

13.1. Waste treatment methods

Recommendation:	Product must be disposed of by special means in accordance with local regulations.
Remains of product:	Remains of product in the tin should be carefully remove and harden using suitable hardener TOUCAN H306, H307, H308. Harden product is not harmfully substance and could be treat like wastes in accordance with regulation. Code of waste: 08 01 11* Do not spill into drainage systems. Waste of this product must be burned in special installations for this purpose or dispose for authorized waste receiver.
Clean tin:	Tin carefully clean is not harmful waste. Code of waste : 15 01 04 Spent packages dispose for authorized receiver who has adequate permission for waste management.
Tin partly empty:	See remains of products. Packs of an article containing residues of hazardous substances or contaminated by a hazardous waste code 15 01 10*

Section 14: Transport information

14.1. UN number

1263

14.2. UN proper shipping name

PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

No applicable



Safety Data Sheet

C200 EURO CLEAR

14.6. Special precautions for user

Land transport: ADR/RID:
Classification code: F1
Tunnels: D1E
Sea transport IMDG: EmS: F-E, S-E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

67/548/EWG (2006/121/WE)
91/155/EWG (2001/58/WE)
1999/45/EC (2006/8/WE)
1991/322/EWG
2000/39/WE
2006/15/WE
2006/1907/WE (REACH)
2004/42/WE
2008/1272/WE (CLP)
Other regulations: ADR (2007-2009), IMDG Code 2006 Edition.

Section 16: Other information

Full text of phrases from 3 point SDS according to CLP
H225 Very flammable liquid and vapour
H226 Flammable liquid and vapour
H312 Harmful in contact with skin
H315 Causes skin irritation
H319 Causes serious eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
EUH066 Repeated exposure may cause skin dryness or cracking
Flam. Liq. 2 Flammable liquid category 2
Flam. Liq. 3 Flammable liquid category 3
STOT SE 3 Specific target organ toxicity – single exposure category 3
Skin Irrit. 2 Skin irritation category 2
Acute Tox. 4* Acute toxicity category 4
Eye Irrit. 2 Eye irritation category 2

The data contained in this Safety Data Sheet are based on our available knowledge at the last revision date. The data contained in this Safety Data Sheet give the conditions of safe use and storage of the product; this document does not give any guarantee as to the properties of the product.