







Features:	Toucan Refinishes Superfil Body-Filler B100 is made from the highest quality raw materials. This lightweight filler is tack-free and has a creamy texture, so it's easy to spread and sand, making it perfect for steel surfaces of any size.																					
Recommended Use:	For leveling large repaired areas and filling small and large dents. For use on steel only.																					
Mixing Ratio: 	100% by vol. Toucan Body Filler 2-3% by vol. Universal Cream Hardener	Part # B100																				
Application: 	Check the surface for moisture or contamination before filling. Spread the filler using a plastic or metal spreader, using slow, firm strokes and applying it in one direction.																					
Drying Times: 	At 20°C (68°F) 15-20 minutes At 60°C (140°F) 5 minutes																					
Surface Preparation: 	Remove rust from metal areas by sanding or sandblasting, then clear the surface with a universal cleaner																					
Sanding:  	Dry sand with P 80-180 grit. Then use a guide coat and fine sand with P 220-240																					
Technical Data:	<table border="0"> <tr> <td>Specific Weight:</td> <td>1.17 kg/l</td> </tr> <tr> <td>Flash Point:</td> <td>104°F</td> </tr> <tr> <td>Solids Vol %:</td> <td>-</td> </tr> <tr> <td>Solids Vol % (RTS):</td> <td>-</td> </tr> <tr> <td>Coverage:</td> <td>-</td> </tr> <tr> <td>Viscosity (RTS):</td> <td>-</td> </tr> <tr> <td>Gloss:</td> <td>Matt</td> </tr> <tr> <td>Color:</td> <td>White</td> </tr> <tr> <td>V.O.C. Regulatory RTS (less water, less exempts):</td> <td>0.8 g/l (0.01 lbs/gal)</td> </tr> <tr> <td>Applicable Use Category:</td> <td>Fillers & Putties</td> </tr> </table>		Specific Weight:	1.17 kg/l	Flash Point:	104°F	Solids Vol %:	-	Solids Vol % (RTS):	-	Coverage:	-	Viscosity (RTS):	-	Gloss:	Matt	Color:	White	V.O.C. Regulatory RTS (less water, less exempts):	0.8 g/l (0.01 lbs/gal)	Applicable Use Category:	Fillers & Putties
Specific Weight:	1.17 kg/l																					
Flash Point:	104°F																					
Solids Vol %:	-																					
Solids Vol % (RTS):	-																					
Coverage:	-																					
Viscosity (RTS):	-																					
Gloss:	Matt																					
Color:	White																					
V.O.C. Regulatory RTS (less water, less exempts):	0.8 g/l (0.01 lbs/gal)																					
Applicable Use Category:	Fillers & Putties																					
Pot Life at 20°C (68°F):	3-5 minutes once activated																					
Remarks:	The use of too much or too little hardener may lead to problems like poor adhesion, soft cure, and poor workability. Too much hardener may result in bleeding or staining. Do not apply on surfaces with contamination or moisture. Do not return the unused mixture to the can as it will harden the remaining contents.																					
Packaging:	Size: 0.75 L																					