



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

TOUCAN P401 PRIMER-SEALER-DTM LV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Universal primer for industrial varnishing

1.3. Details of the supplier of the safety data sheet

COMPANY IDENTITY: Logicar Inc.
COMPANY ADDRESS: 1361 NW 155th DR
COMPANY CITY: Miami, FL 33169
COMPANY PHONE: 305-685-8044

1.4. Emergency telephone number

CHEMTREC: +1(703)527-3887

Section 2: Hazards identification

2.1. Classification of the substance or mixture

The product was classified as dangerous according to Regulation 1272/2008/EC

Classification:

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2 H319

STOT SE 3 H335

STOT SE 3 H336

2.2. Label elements





Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Signal word : DANGER

Hazard statements:

H225 Very flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation.

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

EUH066 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing..

P501 Dispose of contents/container to an authorized waste collection point.

Section 3: Composition/information on ingredients

3.1. Mixtures

Index number	Chemical Name	WE Number	CAS Number	Classification of substance according to CLP	Mark of substance	Weight	Registration Number
607-021-00-X	Methyl acetate	201-185-2	79-20-9	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066	GHS02 GHS07 Dgr H225, H319, H336, EUH066	0 – 10%	01-2119459211-47-XXXX
-	4-chloro- α,α,α -trifluorotoluene	202-681-1	98-56-6	Flam. Liq. 3 H226 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315	GHS02 GHS07 H226, H315, H319, H335	0 – 10%	17-2119942023-50-XXXX
607-025-00-1	Butyl acetate	204-658-1	123-86-4	Flam. Liq. 3 H226 STOT SE 3 H336	GHS02 GHS07 Wng H226, H336, EUH066	0 - 10%	01-2119485493-29-XXXX
601-022-00-9	Xylene	215-535-7	1330-20-7	Flam. Liq. 3 H226 Acute Tox. 4 * H332 Acute Tox. 4 * H312 Skin Irrit. 2 H315	GHS02 GHS07 Wng H226, H312, H315, H332	0 – 10%	01-2119488216-32-XXXX



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Section 4: First aid measures

4.1. Description of first aid measures

General information: See 11 point SDS

Inhalation: Move to fresh air, ensure quiet and warmth, seek medical advice.

Eyes contact: Do not close the eye, rinse with plenty of water (protect) healthy eye, remove contact lenses, seek medical advice.

Skin contact: Immediately remove all contaminated clothing, wash with plenty of water with soap, seek medical advice.

Ingestion: Wash out mouth thoroughly with water. Do not give milk, fat, alcohol. Do not induce the vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Seek medical advice

4.3. Indication of any immediate medical attention and special treatment needed

Seek medical advice

Section 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water, vaporised water, foam, CO₂.

Unsuitable extinguishing media: Tight stream of water.

5.2. Special hazards arising from the substance or mixture

Under the influence of high temperature may produce CO, CO₂ vapours

5.3. Advice for fire-fighters

Firemen have to wear self-contained breathing apparatus and protective clothing. Cool adjacent tanks by spraying water from a safe distance.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Remove ignition sources. Provide for sufficient ventilation. Avoid direct contact with releasing substance (vapours). Avoid contact with eyes and skin. Get acquainted with safety conditions (see point 7 and 8 SDS).

For emergency responders:



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

6.2. Environmental precautions

Keep away from drains, surface-water, ground-water and soil.

6.3. Methods and material for containment and cleaning up

Poured substance should be absorbed with non-flammable materials : sand, silica, special granulated products. Keep to a minimum efflux area. Collect discards, store according to regulations (see point 13 SDS).

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat; keep away from sources of ignition – do not smoke, do not eat, do not drink, do not breathe vapour, avoid contact with skin and eyes. Do not empty under pressure. Use only original tanks.

7.2. Conditions for safe storage, including any incompatibilities

Normal precautions taken when handling flammable substances. Store in hermetically closed containers In temp. 5-25°C. Place of storage should be dry. Protect from heat. Do not store near to sources of ignition.

7.3. Specific end use(s)

Universal primer for industrial varnishing

Section 8: Exposure controls/personal protection

8.1. Control parameters

Limit values for Xylene	TLV: 100 ppm as TWA 150 ppm as STEL A4 (ACGIH 2001). BEI (ACGIH 2001). EU Limit Values: 50 ppm 221 mg/m ³ (8 hours) 100 ppm 442 mg/m ³ (short-term) skin
Limit values for Butyl acetate:	TLV: 150 ppm as TWA 200 ppm as STEL (ACGIH 2003). MAK: 100 ppm 480 mg/m ³

8.2. Exposure controls

Respiratory protection:	Gas mask with "A" type absorbing canister.
Hands protection:	Protective gloves for handling solvents (nitrile rubber).
Eyes protection:	Protective glasses.
Skin protection:	Suitable protective clothing.
Workplace:	Topical stays and exhausting ventilation.



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: thick liquid	Autoignition point: no data
Colour: grey	Vapour pressure: no data
Odour: typical mixture of solvents	Explosion limits: no data
pH: no data	Density: 1,675 g/cm ³
Boiling point: > 56°C	Water solubility: very poor
Melting point: no data	Octanol/Water partition coeff: no data
Flash point: < 0°C	Viscosity: 20±2" DIN Cup 4 (ready for use)
VOC Actual: 282 g/l, 2.35 lbs/gal	VOC Regulatory: 335 g/l, 2.79 lbs/gal

Section 10: Stability and reactivity

10.2. Chemical stability

If handled according to the section 7 product is stable.

10.4. Conditions to avoid

Strong acids and basis, oxidizers, high temperature, peroxides.

10.6. Hazardous decomposition products

Incomplete combustion will produce CO, CO₂ and toxic gases

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity for Xylene:	LD50 (rat, oral) – 4300 mg/kg LC50 (rat, inhalation) – 22100 mg/m ³ (4 h) LD50 (rabbit, rat, skin) – no data
Toxicity for Butyl acetate:	LD50 (rat, oral) – 6400 mg/kg LC50 (rat, inhalation) – 9,6 mg/l (4h) LD50 (rabbit, skin) – >5000 mg/kg
Toxicity for 4-chloro- α,α,α -trifluorotoluene	LD50 (rat, oral) – 6400 mg/kg LC50 (rat, inhalation) – 9,6 mg/l (4h) LD50 (rabbit, skin) – >5000 mg/kg
Toxicity for Methyl acetate:	LD50 (rat, oral) – 5000 mg/kg LD50 (rat, skin) – 2000 mg/kg LC50 (rat, inhalation) > 49mg/l (4h)
Irritating effect:	Skin: irritating and dryness Eyes: irritating



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Symptoms / routes of exposure

Headaches, discomfort, sleepiness, vomiting or may narcotise

Section 12: Ecological information

12.1. Toxicity

Xylene acute toxicity for:	(LC50/96 h) fish – 13500 - 17300 mg/l (LC50//48h) crustacea – 600 mg/l
Butyl acetate acute toxicity for:	(LC50/96 h) fish – 18 mg/l (EC50//48h) crustacea – 32 mg/l
4-chloro- α,α,α -trifluorotoluene acute toxicity for:	(LC50/96 h) fish – 15,9 – 22,9 mg/l (EC50//48h) crustacea – 3,68 mg/l
Methyl acetate acute toxicity for:	(LC50/96 h) fish – 320 mg/l (EC50//48h) crustacea – 1026,7 mg/l

12.6. Other adverse effects

The product is very poorly soluble in water. Do not allow to enter the sewage system, soil, or water reservoirs – inform the local authorities.

Section 13: Disposal considerations

13.1. Waste treatment methods

Remains of product:	Remains of product in the tin should be carefully remove and harden using suitable hardener 30-72 UNIVERSAL HARDENER NORMAL. Harden product is not harmfully substance and could be treat like plastics wastes in accordance with regulation. Code of waste: 08 01 11* Do not spill into drainage systems. Waste of this product must be burned in special installations for this purpose or dispose for authorized waste receiver.
Clean tin:	Tin carefully clean is not harmful waste. Code of waste : 15 01 04 Spent packages dispose for authorized receiver who has adequate permission for waste management.
Tin partly empty:	See remains of products. Packs of an article containing residues of hazardous substances or contaminated by a hazardous waste code 15 01 10*

Section 14: Transport information

14.1. UN number

1263



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

14.2. UN proper shipping name

PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

14.6. Special precautions for user

Land transport: ADR/RID:

Classification code: F1

Tunnels: D1E

Sea transport IMDG: EmS: F-E, S-E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

67/548/EWG (2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

1991/322/EWG

2000/39/WE

2006/15/WE

2006/1907/WE (REACH)

2004/42/WE

2008/1272/WE (CLP)



Safety Data Sheet

P401 PRIMER-SEALER-DTM LV

Section 16: Other information

Other information

Full text of phrases from 3 point SDS according to CLP
H225 Very flammable liquid and vapour
H226 Flammable liquid and vapour
H312 Harmful in contact with skin
H315 Causes skin irritation
H319 Causes serious eye irritation.
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
EUH066 Repeated exposure may cause skin dryness or cracking
Flam. Liq. 2 Flammable liquid category 2
Flam. Liq. 3 Flammable liquid category 3
STOT SE 3 Specific target organ toxicity – single exposure category 3
Acute Tox. 4* Acute toxicity category 4
Skin Irrit. 2 Skin irritation category 2
Eye Irrit. 2 Eye irritation Category 2

Revision Date: 05/29/19

Revision Number: 2