


Technical Data Sheet



Product: Toucan LV Basecoat

Features:	Toucan Basecoat is a Low VOC solvent basecoat, which must be re-coated with any Toucan Clearcoat. The system provides an exceptional optical effect, high durability, resistance to chemicals and lasting gloss. The system meets all USA and Canada VOC regulations.
Benefits:	<ul style="list-style-type: none"> • Excellent Color Matching • Excellent drying • Low consumption • Good flow • Environment safe according to US regulations
Recommended Use:	For painting passenger and commercial vehicles, trucks, etc.
Materials for the job:	<ul style="list-style-type: none"> • Toucan LV Basecoat • Toucan Reducer
Physical properties:	<p>Specific gravity (kg/l): 0.940 to 1.40</p> <p>Flash point: Closed cup: >15°C (>59°F)</p> <p>Vol.% solids: Varies</p> <p>Coverage (Depending on color): 30 -40 µm approx. 7÷9 m²/l</p> <p>Viscosity (RFU): 18s Cup DIN 4</p> <p>Gloss: Matt, Semi matt</p> <p>Color: Various</p> <p>V.O.C. (RTS): <420 g/l (<3.5 lbs/gal)</p>
Pretreatment: 	Remove rust from metal areas by sanding or sand blasting then clean surface with Universal Cleaner. Apply fillers and primers.
Cleaning the equipment:	Wash-up Thinner T60-4
Shelf Life:	Under normal storage conditions minimum two years (unopened tins).

