



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 1: IDENTIFICATION

- 1.1 Product identifier:** H427 4:1 HARDENER NORMAL
- Other means of identification:**  
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses (Professional users): Hardener for coatings  
For Professional users only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**  
  
Logicar Inc.  
1361 NW 155th DR  
FL 33169 Miami - USA  
Phone: 305-685-8044  
info@automotiveartpaints.com  
[https:// www.automotiveartpaints.com](https://www.automotiveartpaints.com)
- 1.4 Emergency phone number:** +1(703)527-3887

### SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**29 CFR 1910.1200:**  
Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200  
Acute Tox. 4: Acute inhalation toxicity, Category 4, H332  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336  
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
Warning
-   
- Hazard statements:**  
H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
- Precautionary statements:**

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 2: HAZARD(S) IDENTIFICATION (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P232: Protect from moisture.  
P234: Keep only in original container.  
P235: Keep cool.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
P410: Protect from sunlight.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

#### Substances that contribute to the classification

Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O); Hexamethylene diisocyanate, oligomers; N-butyl acetate; Isobutyl isobutyrate

#### 2.3 Hazards not otherwise classified (HNOC):

Non-applicable

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances:

Non-applicable

#### 3.2 Mixtures:

**Chemical description:** Mixture composed of chemical products

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

| Identification  | Chemical name/Classification                                                                                                                                         | Concentration        |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| CAS: 28182-81-2 | <b>Hexamethylene diisocyanate, oligomers</b><br>Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning                                                    | <b>45 - &lt;55 %</b> |
| CAS: 28182-81-2 | <b>Hexamethylene diisocyanate, oligomers (&lt;0.1 % O=C=N-R-N=C=O)</b><br>Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning                          | <b>25 - &lt;50 %</b> |
| CAS: 123-86-4   | <b>N-butyl acetate</b><br>Flam. Liq. 3: H226; STOT SE 3: H336 - Warning                                                                                              | <b>15 - &lt;25 %</b> |
| CAS: 97-85-8    | <b>Isobutyl isobutyrate</b><br>Flam. Liq. 3: H226; STOT SE 3: H336 - Warning                                                                                         | <b>&lt;10 %</b>      |
| CAS: 1330-20-7  | <b>Xylene</b><br>Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2A: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | <b>&lt;5 %</b>       |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST-AID MEASURES

#### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 4: FIRST-AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### **By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### **By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### **4.2 Most important symptoms / effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

#### **4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

### SECTION 5: FIRE-FIGHTING MEASURES

#### **5.1 Suitable (and unsuitable) extinguishing media:**

##### **Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

##### **Unsuitable extinguishing media:**

Water jet

#### **5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### **5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

##### **Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1 Personal precautions, protective equipment and emergency procedures:**

##### **For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### **For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

#### **6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### **6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 9 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### Other information:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Protect from moisture. Keep only in original container. Keep cool. Protect from sunlight.

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

- CONTINUED ON NEXT PAGE -

## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

| Identification                          | Occupational exposure limits |         |                       |
|-----------------------------------------|------------------------------|---------|-----------------------|
| N-butyl acetate<br>CAS: 123-86-4        | 8-hour TWA PEL               | 150 ppm | 710 mg/m <sup>3</sup> |
|                                         | Ceiling Values - TWA PEL     |         |                       |
| Xylene <sup>(1)</sup><br>CAS: 1330-20-7 | 8-hour TWA PEL               | 100 ppm | 435 mg/m <sup>3</sup> |
|                                         | Ceiling Values - TWA PEL     |         |                       |

US. ACGIH Threshold Limit Values (2022):

| Identification                          | Occupational exposure limits |         |  |
|-----------------------------------------|------------------------------|---------|--|
| N-butyl acetate<br>CAS: 123-86-4        | TLV-TWA                      | 20 ppm  |  |
|                                         | TLV-STEL                     |         |  |
| Xylene <sup>(1)</sup><br>CAS: 1330-20-7 | TLV-TWA                      | 100 ppm |  |
|                                         | TLV-STEL                     | 150 ppm |  |

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

| Identification                          | Occupational exposure limits |         |                       |
|-----------------------------------------|------------------------------|---------|-----------------------|
| N-butyl acetate<br>CAS: 123-86-4        | PEL                          | 150 ppm | 710 mg/m <sup>3</sup> |
|                                         | STEL                         | 200 ppm | 950 mg/m <sup>3</sup> |
| Xylene <sup>(1)</sup><br>CAS: 1330-20-7 | PEL                          | 100 ppm | 435 mg/m <sup>3</sup> |
|                                         | STEL                         | 150 ppm | 655 mg/m <sup>3</sup> |

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

| Identification                   | Occupational exposure limits |          |  |
|----------------------------------|------------------------------|----------|--|
| N-butyl acetate<br>CAS: 123-86-4 | TWA                          |          |  |
|                                  | IDLH Value                   | 1700 ppm |  |

<sup>(1)</sup> Skin

#### Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

| Identification           | BEIs®                  | Determinant                   | Sampling Time |
|--------------------------|------------------------|-------------------------------|---------------|
| Xylene<br>CAS: 1330-20-7 | 1500 mg/g (Creatinine) | Methylhippuric acids in urine | End of shift  |

### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

| Pictogram                                                                                                                     | PPE                                                | Remarks                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR) |

C.- Specific protection for the hands

| Pictogram                                                                                                        | PPE                                       | Remarks                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory hand protection | NON-disposable chemical protective gloves | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR) |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### D.- Eye and face protection

| Pictogram                                                                                                      | PPE         | Remarks                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory face protection | Face shield | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR) |

#### E.- Bodily protection

| Pictogram                                                                                                               | PPE                                                                                                 | Remarks                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <br>Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | For professional use only. Clean periodically according to the manufacturer's instructions. |
| <br>Mandatory foot protection          | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | Replace boots at any sign of deterioration.                                                 |

#### F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure                                                                                       | Standards                                       | Emergency measure                                                                                        | Standards                                      |
|---------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

VOC Regulatory:

V.O.C. at 68 °F: 4.15 lbs/gal (497 g/L)

VOC Actual:

V.O.C. at 68 °F: 4.15 lbs/gal (497 g/L)

#### Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

##### Appearance:

|                          |                  |
|--------------------------|------------------|
| Physical state at 68 °F: | Liquid           |
| Appearance:              | Fluid            |
| Color:                   | Colorless        |
| Odor:                    | Characteristic   |
| Odour threshold:         | Non-applicable * |

##### Volatility:

|                                        |                       |
|----------------------------------------|-----------------------|
| Boiling point at atmospheric pressure: | 282 °F                |
| Vapour pressure at 68 °F:              | 781 Pa                |
| Vapour pressure at 122 °F:             | 4027.69 Pa (4.03 kPa) |
| Evaporation rate at 68 °F:             | Non-applicable *      |

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

#### Product description:

|                                              |                               |
|----------------------------------------------|-------------------------------|
| Density at 68 °F:                            | 1005 - 1025 kg/m <sup>3</sup> |
| Relative density at 68 °F:                   | 1.005 - 1.025                 |
| Dynamic viscosity at 68 °F:                  | Non-applicable *              |
| Kinematic viscosity at 68 °F:                | Non-applicable *              |
| Kinematic viscosity at 104 °F:               | Non-applicable *              |
| Concentration:                               | Non-applicable *              |
| pH:                                          | Non-applicable *              |
| Vapour density at 68 °F:                     | Non-applicable *              |
| Partition coefficient n-octanol/water 68 °F: | Non-applicable *              |
| Solubility in water at 68 °F:                | Non-applicable *              |
| Solubility properties:                       | Non-applicable *              |
| Decomposition temperature:                   | Non-applicable *              |
| Melting point/freezing point:                | Non-applicable *              |

#### Flammability:

|                            |                  |
|----------------------------|------------------|
| Flash Point:               | 94 °F            |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature:  | 599 °F           |
| Lower flammability limit:  | Non-applicable * |
| Upper flammability limit:  | Non-applicable * |

#### Particle characteristics:

|                             |                  |
|-----------------------------|------------------|
| Median equivalent diameter: | Non-applicable * |
|-----------------------------|------------------|

#### 9.2 Other information:

##### Information with regard to physical hazard classes:

|                                                              |                  |
|--------------------------------------------------------------|------------------|
| Explosive properties:                                        | Non-applicable * |
| Oxidising properties:                                        | Non-applicable * |
| Corrosive to metals:                                         | Non-applicable * |
| Heat of combustion:                                          | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

##### Other safety characteristics:

|                           |                  |
|---------------------------|------------------|
| Surface tension at 68 °F: | Non-applicable * |
| Refraction index:         | Non-applicable * |

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 10: STABILITY AND REACTIVITY (continued)

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

#### 10.5 Incompatible materials:

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

##### B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Hydrocarbons, C9, aromatics (3); Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

##### F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

##### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Repeated exposure may cause skin dryness or cracking

- CONTINUED ON NEXT PAGE -





## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

| Identification                                                                  | Acute toxicity         |                 | Genus  |
|---------------------------------------------------------------------------------|------------------------|-----------------|--------|
| N-butyl acetate<br>CAS: 123-86-4                                                | LD50 oral              | 12789 mg/kg     | Rat    |
|                                                                                 | LD50 dermal            | 14112 mg/kg     | Rabbit |
|                                                                                 | LC50 inhalation vapour | 23.4 mg/L (4 h) | Rat    |
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2 | LD50 oral              | 2660 mg/kg      | Rat    |
|                                                                                 | LD50 dermal            |                 |        |
|                                                                                 | LC50 inhalation vapour | 11 mg/L         |        |
| Hexamethylene diisocyanate, oligomers<br>CAS: 28182-81-2                        | LD50 oral              | 5100 mg/kg      | Rat    |
|                                                                                 | LD50 dermal            |                 |        |
|                                                                                 | LC50 inhalation vapour | 11 mg/L         |        |
| Isobutyl isobutyrate<br>CAS: 97-85-8                                            | LD50 oral              | 12800 mg/kg     | Rat    |
|                                                                                 | LD50 dermal            |                 |        |
|                                                                                 | LC50 inhalation vapour |                 |        |
| Xylene<br>CAS: 1330-20-7                                                        | LD50 oral              | 2100 mg/kg      | Rat    |
|                                                                                 | LD50 dermal            | 1100 mg/kg      | Rat    |
|                                                                                 | LC50 inhalation vapour | 17 mg/L         | Rat    |

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### 12.1 Ecotoxicity (aquatic and terrestrial, where available):

##### Acute toxicity:

| Identification                                                                  | Concentration |                       | Species                 | Genus      |
|---------------------------------------------------------------------------------|---------------|-----------------------|-------------------------|------------|
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2 | LC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | 1000 mg/L (72 h)      | Scenedesmus subspicatus | Algae      |
| Hexamethylene diisocyanate, oligomers<br>CAS: 28182-81-2                        | LC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | 1000 mg/L (72 h)      | Scenedesmus subspicatus | Algae      |
| N-butyl acetate<br>CAS: 123-86-4                                                | LC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | Non-applicable        |                         |            |
|                                                                                 | EC50          | 675 mg/L (72 h)       | Scenedesmus subspicatus | Algae      |
| Isobutyl isobutyrate<br>CAS: 97-85-8                                            | LC50          | >10 - 100 mg/L (96 h) |                         | Fish       |
|                                                                                 | EC50          | >10 - 100 mg/L (48 h) |                         | Crustacean |
|                                                                                 | EC50          | >10 - 100 mg/L (72 h) |                         | Algae      |
| Xylene<br>CAS: 1330-20-7                                                        | LC50          | >10 - 100 mg/L (96 h) |                         | Fish       |
|                                                                                 | EC50          | >10 - 100 mg/L (48 h) |                         | Crustacean |
|                                                                                 | EC50          | >10 - 100 mg/L (72 h) |                         | Algae      |

##### Chronic toxicity:

| Identification                   | Concentration |                | Species       | Genus      |
|----------------------------------|---------------|----------------|---------------|------------|
| N-butyl acetate<br>CAS: 123-86-4 | NOEC          | Non-applicable |               |            |
|                                  | NOEC          | 23.2 mg/L      | Daphnia magna | Crustacean |

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Concentration |           | Species             | Genus      |
|----------------|---------------|-----------|---------------------|------------|
| Xylene         | NOEC          | 1.3 mg/L  | Oncorhynchus mykiss | Fish       |
| CAS: 1330-20-7 | NOEC          | 1.17 mg/L | Ceriodaphnia dubia  | Crustacean |

#### 12.2 Persistence and degradability:

##### Substance-specific information:

| Identification                   | Degradability |                | Biodegradability |                |
|----------------------------------|---------------|----------------|------------------|----------------|
| N-butyl acetate<br>CAS: 123-86-4 | BOD5          | Non-applicable | Concentration    | Non-applicable |
|                                  | COD           | Non-applicable | Period           | 5 days         |
|                                  | BOD5/COD      | Non-applicable | % Biodegradable  | 84 %           |
| Xylene<br>CAS: 1330-20-7         | BOD5          | Non-applicable | Concentration    | Non-applicable |
|                                  | COD           | Non-applicable | Period           | 28 days        |
|                                  | BOD5/COD      | Non-applicable | % Biodegradable  | 88 %           |

#### 12.3 Bioaccumulative potential:

##### Substance-specific information:

| Identification                   | Bioaccumulation potential |      |
|----------------------------------|---------------------------|------|
| N-butyl acetate<br>CAS: 123-86-4 | BCF                       | 4    |
|                                  | Pow Log                   | 1.78 |
|                                  | Potential                 | Low  |
| Xylene<br>CAS: 1330-20-7         | BCF                       | 9    |
|                                  | Pow Log                   | 2.77 |
|                                  | Potential                 | Low  |

#### 12.4 Mobility in soil:

| Identification                       | Absorption/desorption |                      | Volatility |                               |
|--------------------------------------|-----------------------|----------------------|------------|-------------------------------|
| N-butyl acetate<br>CAS: 123-86-4     | Koc                   | Non-applicable       | Henry      | Non-applicable                |
|                                      | Conclusion            | Non-applicable       | Dry soil   | Non-applicable                |
|                                      | Surface tension       | 2.478E-2 N/m (77 °F) | Moist soil | Non-applicable                |
| Isobutyl isobutyrate<br>CAS: 97-85-8 | Koc                   | Non-applicable       | Henry      | Non-applicable                |
|                                      | Conclusion            | Non-applicable       | Dry soil   | Non-applicable                |
|                                      | Surface tension       | 2.256E-2 N/m (77 °F) | Moist soil | Non-applicable                |
| Xylene<br>CAS: 1330-20-7             | Koc                   | 202                  | Henry      | 524.86 Pa·m <sup>3</sup> /mol |
|                                      | Conclusion            | Moderate             | Dry soil   | Yes                           |
|                                      | Surface tension       | Non-applicable       | Moist soil | Yes                           |

#### 12.5 Results of PBT and vPvB assessment:

Non-applicable

#### 12.6 Other adverse effects:

Not described

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Ignitability. The next EPA hazardous waste number could apply: D001.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

##### Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

##### Regulations related to waste management:

Legislation related to waste management:

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 13: DISPOSAL CONSIDERATIONS (continued)

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
Labels: 3  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

#### Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
Labels: 3  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Special regulations: 163, 223, 955, 367  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
Labels: 3  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *N-butyl acetate (123-86-4)* ; *Xylene (1330-20-7)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): *Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O) (28182-81-2)* ; *Hexamethylene diisocyanate, oligomers (28182-81-2)* ; *N-butyl acetate (123-86-4)* ; *Isobutyl isobutyrate (97-85-8)* ; *Xylene (1330-20-7)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *N-butyl acetate (123-86-4)* - 5000 lb ; *Xylene (1330-20-7)* - U239
- Hazardous Air Pollutants (Clean Air Act): *Xylene (1330-20-7)*
- Massachusetts RTK - Substance List: *Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O) (28182-81-2)* ; *Hexamethylene diisocyanate, oligomers (28182-81-2)* ; *N-butyl acetate (123-86-4)* ; *Xylene (1330-20-7)*
- Minnesota - Hazardous substances ERTK: *N-butyl acetate (123-86-4)* ; *Xylene (1330-20-7)*
- New Jersey Worker and Community Right-to-Know Act: *N-butyl acetate (123-86-4)* ; *Isobutyl isobutyrate (97-85-8)* ; *Xylene (1330-20-7)*
- New York RTK - Substance list: *N-butyl acetate (123-86-4)* ; *Isobutyl isobutyrate (97-85-8)* ; *Xylene (1330-20-7)*
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: Non-applicable
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O) (28182-81-2)* ; *Hexamethylene diisocyanate, oligomers (28182-81-2)* ; *N-butyl acetate (123-86-4)* ; *Isobutyl isobutyrate (97-85-8)* ; *Xylene (1330-20-7)*
- Rhode Island - Hazardous substances RTK: *N-butyl acetate (123-86-4)* ; *Xylene (1330-20-7)*
- SB-258 Cleaning Product Right to Know Act : Non-applicable
- The Toxic Substances Control Act (TSCA) : *Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O) (28182-81-2)* ; *Hexamethylene diisocyanate, oligomers (28182-81-2)* ; *N-butyl acetate (123-86-4)* ; *Isobutyl isobutyrate (97-85-8)* ; *Xylene (1330-20-7)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *Xylene (1330-20-7)*

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

#### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

#### Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H317: May cause an allergic skin reaction.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H332: Harmful if inhaled.

H226: Flammable liquid and vapour.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### 29 CFR 1910.1200:

- CONTINUED ON NEXT PAGE -



## H427 4:1 HARDENER NORMAL

Date of compilation: 9/8/2025

Version: 1

### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Acute Tox. 4: H332 - Harmful if inhaled.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2A: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

#### Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

#### Abbreviations and acronyms:

IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
CL50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon  
IARC: International Agency for Research on Cancer

Date of compilation: 9/8/2025

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET